

DATA SHEET


SV 300/2

SIDE CHANNEL BLOWERS

double stage
air-cooled

MAKE IT BECKER.








- 1 Vacuum connection (G2½)
- 2 Pressure connection (G2½)
- 3 Optional vibration dampers (rubber buffer) for vertical installation
- * Device dimensions without pedestal under the silencer, with rubber buffers on the enclosure cover
- The motor illustration may vary
- Dimensions in mm [inch]

Blast air rate		Pressure relative		Motors		Emission sound pressure level ¹⁾		Weight with motor	L
m³/h		mbar		kW		dB(A)		kg	mm [inch]
50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz		
160	190	+330	+280	2.2	2.65	69.2 (+265 mbar)	66.9 (+200 mbar)	42.5	469 [18.5]
160	190	+515	+450	3.0	3.6	71.7 (+330 mbar)	72.0 (+330 mbar)	45.0	494 [19.5]

¹⁾ According to DIN EN ISO 11203, accuracy class of measurement: class 2, extended measurement uncertainty: 3 dB
1 m [39.4 inch] distance, at medium load, both connection sides piped


3~ Motors											
#	50 Hz					60 Hz					Version
	kW	V		min ⁻¹	A	kW	V		min ⁻¹	A	
01	2.2	Δ230/Y400	IE3	2910	7.7/4.45	2.65	Δ265/Y460 Δ230/Y400	IE3	3510 3460	7.6/4.4 8.3/4.6	UL • CSA IP55 • ISO F • bimetal
02						2.65	YY230/Y460 YY208/Y –	IE3	3510 3460	8.6/4.3 9.2/ –	UL • CSA • CC IP55 • ISO F • bimetal
03	3.0	Δ230/Y400	IE3	2890	10.6/6.1	3.6	Δ265/Y460 Δ230/Y400	IE3	3500 3460	10.6/6.1 11.6/6.7	UL • CSA IP55 • ISO F • bimetal
04						3.6	YY230/Y460 YY208/Y –	IE3	3510 3480	12.4/6.2 13.0/ –	UL • CSA • CC IP55 • ISO F • bimetal
05	3.0	Δ200/Y350	IE3	2920	13.9/8.0	3.6	Δ220/Y380–400 Δ200/Y350	IE3	3500 3470	12.6/7.3 13.2/7.6	IP55 • ISO F • bimetal



Reference data (atmosphere): 1000 mbar (100 kPa), 20°C (68°F)
Tolerance: ±10%
Temperature: Inlet air 0°C ... 40°C (32°F ... 104°F), Ambient air -10°C ... 40°C (14°F ... 104°F)


+ VARIANTS AND ACCESSORIES

PRESSURE SAFETY VALVE




SUCTION FILTER

- Paper or polyester insert



SUCTION FILTER AND PRESSURE SAFETY VALVE




- Dimensions in mm [inch] – For other dimensions, see the figure on page 2.

ATEX SV 300/2 WITH MOTOR

- With coupling for flange motor
- The motor must be supported!


ATEX zone	Blast air rate m³/h (50 Hz)	Pressure relative mbar (50 Hz)
II 3G/3G c IIB T3 II 3D c IIB T 125	160	+480
II 3G/3G c IIB T3 II 3D c IIB T 190	160	+515

50 Hz				Total weight kg
kW	V	min ⁻¹	A	
3.3	Δ230/Y400	2830	10.6/6.12	71




WITHOUT MOTOR

- With coupling for flange motor
- The motor must be supported!



WITHOUT MOTOR

- With free shaft end
- Max. 5600 rpm with V-belt pulley
- Possible performance data see VARIAR SV 300/2¹⁾



OTHER VARIANTS AND ACCESSORIES

- With increased corrosion protection
- VARIAR SV 300/2 with frequency inverter VAU7.5/3 for 100 Hz operation¹⁾
- VARIAR SV 300/2 gas-tight (inert gases) with frequency inverter VAU7.5/3 for 100 Hz operation¹⁾
- Sound proof box SH 18¹⁾

¹⁾ See separate data sheet

- Type plate data on current consumption and rotation speed of the motors may vary. Tolerance -1.5/+2% in each case. The motor illustration may vary.
- Dimensions in inch – For other dimensions, see the figure on page 2.



Sound proof box SH 18



MAKE IT BECKER.