

DATA SHEET

SV 700/1


SIDE CHANNEL BLOWERS

single stage

air-cooled

MAKE IT BECKER.








- 1 Vacuum connection (G4)
- 2 Pressure connection (G4)
- 3 Rubber buffer position (optional)
- * Device dimensions without pedestal under the silencer, with rubber buffers on the enclosure cover
- The motor illustration may vary
- Dimensions in mm [inch]

Blast air rate		Pressure relative		Motors		Emission sound pressure level ¹⁾		Weight with motor
m³/h		mbar		kW		dB(A)		kg
50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	
750	900	+185	+150	5.5	6.6	71 (+125 mbar)	72 (+100 mbar)	89
750	900	+285	+250	7.5	9.0	72 (+190 mbar)	74 (+170 mbar)	112
750	900	+400	+400	11.0	13.2	73 (+270 mbar)	75 (+270 mbar)	119

¹⁾ According to DIN EN ISO 11203, accuracy class of measurement: class 2, extended measurement uncertainty: 3 dB
1 m [39.4 inch] distance, at medium load, both connection sides piped

3~ Motors												L
#	50 Hz					60 Hz				Version	mm [inch]	
	kW	V		min ⁻¹	A	kW	V	min ⁻¹	A			
01	5.5	Δ400/Y690	IE3	2930	11.9/6.9	6.6	Δ460	IE3	3520	11.5	UL • CSA	563 [22.2]
						5.5	Δ400/Y690	IE3	3520	10.2/5.9	IP55 • ISO F • bimetal	
02						6.6	Δ230/Y400	IE3	3496	20.6/11.9	UL • CSA • CC IP55 • ISO F • bimetal	561 [22.1]
							Δ265/Y460	IE3	3528	19.9/11.5		
							Δ208		3470	22.5		
03	5.5	Δ200/Y350	IE3	2935	26.9/15.4	6.6	Δ220/Y380–400	IE3	3530	24.0/13.9–14.3	IP55 • ISO F • bimetal	563 [22.2]
							Δ200/Y350	IE3	3500	24.7/14.1		
04						6.6	Δ400/Y690	IE3	3524	14.2/8.3	UL • CSA • CC IP65 • ISO F • bimetal	557 [21.9]
05	7.5	Δ400	IE3	2910	13.5	9.0	Δ460	IE3	3500	13.9	UL • CSA	614 [24.2]
							Δ400		3450	16.1	IP55 • ISO F • bimetal	
06						9.0	YY230/Y460	IE3	3505	27.8/13.9	UL • CSA IP55 • ISO F • bimetal	614 [24.2]
							YY208		3475	30.7		
07	7.5	Δ200/Y350	IE3	2920	27.0/15.6	9.0	Δ220/Y380–400	IE3	3500	29.1/16.8	IP55 • ISO F • bimetal	614 [24.2]
							Δ200/Y350		3465	31.7/18.3		
08	11.0	Δ400	IE3	2930	21.8	13.2	Δ460	IE3	3525	21.9	UL • CSA IP55 • ISO F • bimetal	635 [25.0]
							Δ400		3490	23.7		
09						13.2	YY230/Y460	IE3	3530	44.8/22.4	UL • CSA IP55 • ISO F • bimetal	635 [25.0]
							YY208		3505	46.5		
10	11.0	Δ200/Y350	IE3	2920	41.4/23.9	13.2	Δ220/Y380–400	IE3	3510	43.3/25.0	IP55 • ISO F • bimetal	635 [25.0]
							Δ200/Y350		3465	46.8/27.0		

• Type plate data on current consumption and rotation speed of the motors may vary. Tolerance -1.5/+2% in each case.




Reference data (atmosphere): 1000 mbar (100 kPa), 20°C (68°F)
Tolerance: ±10%
Temperature: Ambient air -10°C ... 40°C (14°F ... 104°F), Inlet air 0°C ... 40°C (32°F ... 104°F)

+ VARIANTS AND ACCESSORIES

WITHOUT MOTOR

- With coupling for flange motor
- Standard DIN EN 50347
- Flange size FF265
- Shaft end Ø38x80 mm [≈1,5x3,2 inch]
- Max. size BG160
- The motor must be supported!



OTHER VARIANTS AND ACCESSORIES

- VARIAIR SV 700/1 with frequency inverter VAU11-22/3 for 80 Hz operation¹⁾
- External suction filter
- External pressure safety valve
- With increased corrosion protection



VARIAIR SV 700/1



Example for an external suction filter

¹⁾ See separate data sheet

- Dimensions in mm [inch] – For other dimensions, see the figure on page 2.
- Possible combinations on request



MAKE IT BECKER.